



Power Device

RE.99.PPOE

THE FUTURE IS HERE. IT'S JUST NOT DISTRIBUTED YET



Document: RE.99.PPOE Date:15-January-2010 Version: 1.5

Passive Power Over Ethernet

The RE.99.PPOE universal 20 Watt PoE power supply provides power to devices through RJ45 jacks and data over a single Ethernet cable. This compact, self-contained device provides an efficient and cost-effective solution to systems designers confronting the need for additional electrical outlets or the placement of network access points.

Features

- ✓ 100-250 VAC Universal Input
- ✓ Desktop Style
- ✓ Single Output up to 20W
- ✓ Compliant with passive IEEE 802.3af standard
- ✓ Regulated Output With Low Ripple
- ✓ Meets Safety Agency Requirements
- ✓ Complies With EMI/RFI Regulations
- ✓ CE, RoHS and WEEE Compliant
- ✓ Impact Resistant Polycarbonate Enclosure
- ✓ 1 Year Warranty

Specifications

Input Specifications

Voltage	100-250 VAC -10%, +6%
Line Frequency	47 - 63 Hz Current 0.5A max. at 90 VAC input
Protection	Internal primary current fuse, Inrush limiting
Inlet type	IEC320-C14

Output Specifications

Combined Line and Load Voltage Regulation	±1% excluding cord
Ripple	1% V p-p max for output current of >0.175A
Transient Response	0.5 msec. for 50% load change typical
Holdup Time	18 msec min. @120 VAC 60 msec min. @240 VAC
Protection	Foldback overcurrent protection Short Circuit Protection
Cord and Connector	Dual RJ45 jacks built into the enclosure

Safety Approvals

Agency Listings	cULus: UL/CSA60950; TUV: EN60950; CE: LVD, EMC
-----------------	--

Electrical

Topology	Switching - Fixed frequency fly back
Dielectric Withstand	3000 VAC, 4250 VDC primary-secondary 500 VDC secondary-ground
Spacing	6.4mm primary-secondary
Leakage Current	Less than 750 uA
Efficiency	Minimum 65%
EMI	Complies with EMC Directives
CE	CE Compliant
MTBF	100,000 Calculated Hours

Environmental

Operating Temperature	0° to 40°C with no derating
Storage Temperature	-30° to +85°C
Relative Humidity	5% to 95% non-condensing
Altitude	0-10,000 feet
Cooling	Convectional - non vented case

Mechanical

Case Dimensions	107.9L x 66.5W x 38.6H (mm)
Case Material	Black, 94V0 Polycarbonate
Weight	7 Ounces, 198 grams



All information contained herein is believed to be accurate and is subject to change without notice. No responsibility is assumed for its use. RFI Engineering reserves the right to make changes without notice, design, product components, and product manufacturing methods. Copyright 2010 All Rights Reserved RFI Engineering B.V., Markerkant 13-76, 1314 AN Almere, The Netherlands, info@rfi-engineering.com